

STANDARD SYSTEM FEATURES

- 1) **1 PVC sea strainer**
2 3/4" NPT x 5/8" barbed hose connection
- 2) **Pre-Filter** complete with 20 micron cartridge (5 and 20 micron with optional boost pump)
1 Stainless steel bracket with 8 screws
1 Service valve with 1 Nylon nipple and 3 barbed hose connectors (with boost pump) or
1 flush/storage valve with 1 Nylon nipple and 1 NPT female tee (without boost pump)
1 Filter wrench
- 3) **1 High-pressure pump unit** with vibration dampers
- 4) **1 Pressure vessel with reverse osmosis membrane**
- 5) **1 Stainless steel control panel** completely assembled with
1 Pressure control valve
1 High pressure gauge
1 Product flow meter
1 Diverter (3-way) valve
1 Breaker (without boost pump) or
2 Breakers (with boost pump)
- 6) **1 Hardener / pH neutralizer kit** with mineral element and 2pcs 3/8" compression fittings
1 Stainless steel bracket with 8 screws
- 7) 15 feet / 4.5 meter high pressure hose with 2 x stainless steel high pressure fittings attached
2 x stainless steel field attachable high pressure fittings
- 8) 20 feet / 6 meter 3/8" blue product water tubing
10 feet / 3 meter 5/8" braided intake hose
10 feet / 3 meter 1/2" braided reject hose or 10 mm tubing
- 9) 17 Stainless steel hose clamps (with boost pump) or
12 Stainless steel hose clamps (without boost pump)